

Enclosures **Commander Series****Polycarbonate Enclosure 4 x 3 x 2 Inches Commander Series Slim****Catalog Number** **COPC432****UPC** **191564103877.0**

List Price

**\$73.45****Description**

4H x 3W x 2D Inches Commander Series Polycarbonate Enclosures are slim-line designed enclosures featuring 4 cover screws with a blank lift off cover.

**Application**

For use in many MRO and OEM applications

**Features**

- Memory retaining continuous polyurethane gasket
- Captive polymer cover screws on polycarbonate option
- Submersible; non corrosive; environmental design
- High Impact Resistance



## General Information

---

<b>Color</b>	Gray
<b>Cover Type</b>	Opaque
<b>Mounting Type</b>	Wall Mount
<b>Material</b>	Polycarbonate
<b>Cover Screw Size</b>	Custom
<b>Cover Screw Recommended Torque</b>	16-20 in-lbs.
<b>Cover Screw Material</b>	Polycarbonate
<b>Installation Mounting Torque</b>	25-30 in-lbs. Max
<b>Metal Inserts</b>	None
<b>Gasket Material</b>	Poured In Place (PIP) Polyurethane Seamless
<b>Country of Origin</b>	USA

## Dimensions

---

<b>Height (in)</b>	4.0
<b>Width (in)</b>	3.0
<b>Depth (in)</b>	2.0
<b>Height (mm)</b>	102.0
<b>Width (mm)</b>	76.0
<b>Depth (mm)</b>	51.0
<b>Useable Depth (in)</b>	2.5
<b>Useable Depth (mm)</b>	64.0

## Standards

---

**NEMA 250; UL 50; UL 50e;  
UL508A** cULus Listed File #E64358

**Type** 1; 3R; 4; 4X; 6; 6P; 12

**IEC 60529** IP66; IP68

**IEC 60529** cULus Listed File #E362920

**Temperature Range °F** -40°F to +248°F

**Temperature Range °C** -40°C to +120°C

**Flammability Rating** UL94-5VA

**Outdoor Exposure UL746c** (f1) Rated

**CE** Certified