

Enclosures **Commander Series**

## Polycarbonate Enclosure 5 x 3 x 3 Inches Commander Yellow Push Button



**Catalog Number** YW-COPC2PB

**UPC** 19156411711

List Price

**\$108.47**

### Description

5H x 3W x 3D Inches Yellow Push Button Commander Series Polycarbonate Enclosures are slim-line designed enclosures featuring 4 cover screws with a lift off cover. This design has 2 holes at 30 mm.

### Application

For use in many MRO and OEM applications

### Features

- Memory retaining continuous polyurethane gasket
- Captive polymer cover screws on polycarbonate option
- Submersible; non corrosive; environmental design
- High Impact Resistance
- High visibility safety yellow cover
- High visibility safety yellow cover



## General Information

---

|                                       |  |
|---------------------------------------|--|
| <b>Color</b>                          | Yellow   |
| <b>Cover Type</b>                     | Push Button                                    |
| <b>Mounting Type</b>                  | Wall Mount                                     |
| <b>Material</b>                       | Polycarbonate                                  |
| <b>Cover Screw Size</b>               | Custom   |
| <b>Cover Screw Recommended Torque</b> | 16-20 in-lbs.                                  |
| <b>Cover Screw Material</b>           | Polycarbonate                                  |
| <b>Installation Mounting Torque</b>   | 25-30 in-lbs. Max                              |
| <b>Metal Inserts</b>                  |  |
| <b>Gasket Material</b>                | Poured In Place (PIP)<br>Polyurethane Seamless |
| <b>Country of Origin</b>              | USA  |

## Dimensions

---

|                           |       |
|---------------------------|-------|
| <b>Height (in)</b>        | 5.0   |
| <b>Width (in)</b>         | 3.0   |
| <b>Depth (in)</b>         | 3.0   |
| <b>Height (mm)</b>        | 127.0 |
| <b>Width (mm)</b>         | 76.0  |
| <b>Depth (mm)</b>         | 76.0  |
| <b>Useable Depth (in)</b> | 3.3   |
| <b>Useable Depth (mm)</b> | 83.0  |

## Standards

---

|  |                            |
|--|----------------------------|
| <b>NEMA 250; UL 50; UL 50e; UL508A</b> | cULus Listed File #E64358  |
| <b>Type</b>                            | 1; 3R; 4; 4X; 6; 6P; 12    |
| <b>IEC 60529</b>                       | IP66; IP68                 |
| <b>IEC 60529</b>                       | cULus Listed File #E362920 |
| <b>Temperature Range °F</b>            | -40°F to +248°F            |
| <b>Temperature Range °C</b>            | -40°C to +120°C            |
| <b>Flammability Rating</b>             | UL94-5VA                   |
| <b>Outdoor Exposure UL746c</b>         | (f1) Rated                 |
| <b>CE</b>                              | Certified                  |