

Accessories **HMI Covers**

SolarShield HMI Cover 10 x 8 Inch Opaque Cover

Catalog Number HMICVR1008

UPC 19156411932

List Price

\$218.81

Description


10W x 8H Inch SolarShield HMI Opaque Cover for HMI Device Type 4 and 4X, Non-Metallic

Application

- Provide superior protection of Human Machine Interface (HMI) screens from the sun, wind-blown dust, and other environmental conditions
- Extremely tough and durable, HMI Covers are used in both outdoor and indoor applications
- Non-hazardous industrial and commercial applications
- Oil and gas, Equipment manufacturing, Industrial machines, Water/Wastewater, marine, food and beverage applications

Features

- Fits standard 10" x 8" and smaller HMI screens
- Maintains NEMA 4/4X rating of enclosure when paired with NEMA 4/4X rated HMI Device
- Patent pending with non-metallic, hinged inner doors to shield screen from the sun and allow for hands-free use
- Universal covers can be used with either non-metallic or metallic enclosures
- Lightweight, high-Impact rated, UV resistant polycarbonate material construction
- Stainless steel hardware kit Included
- Padlock-able for increased security
- Simple and easy installation with the use of common tools
- Available as standalone SKUs or assembled to our enclosures with



added HMI cutouts through our value-add ModRight program.

- Color: Pantone 428C

General Information

Color	Gray
Cover Type	Opaque
Mounting Type	Box Mount
Material	Polycarbonate
Cover Screw Size	#10-32 x 5/8
Cover Screw Recommended Torque	20-24 in-lbs
Cover Screw Material	304 SS
Installation Mounting Torque	20-24 in-lbs Max
Hinge Material	Integral Polycarbonate
Latch Material	Nylon
Gasket Material	Poured In Place (PIP) Polyurethane Seamless
Country of Origin	India

Dimensions

Height (in)	11.41
Width (in)	13.13
Depth (in)	2.5
Height (in)	334
Width (in)	290
Depth (in)	64
Inside Height (in)	9.88
Inside Width (in)	7.25
Inside Depth (in)	2.5

Standards

UL508A	cURus Registered Component File #E64358
Type	4; 4X when Used with 4/4X HMI Device
Temperature Range °F	-40°F to +248°F
Temperature Range °C	-40°C to +120°C
Flammability Rating	UL94-5VA
Outdoor Exposure UL746c	(f1) Rated