

Enclosures **BantamBox Series**

## Polycarbonate Enclosure 8 x 6 x 4 Inches BantamBox Clear Cover



**Catalog Number** BBCC201510W

**UPC** 191564105376

List Price

**\$103.40**

### Description

8H x 6W x 4D Inches BantamBox Series polycarbonate enclosures feature flush sides making it a sought-after enclosure for OEM designs. Raised bosses accommodate back panel mounting and are successfully used for remote sensor mounting and small electronic controls in any environment. This configuration features a clear lift off cover with 4 cover screws.



### Application

Small; simple design ideal for OEMs in the electronics market; circuit boards and wiring applications

### Features

- Available in 2 cover options: 1. Opaque Cover; 2. Clear Polycarbonate Cover
- Multiple depths available in most sizes
- Resistant to harsh environments
- Flush sides for optimal fit
- Multiple molded in bosses for a variety of mounting solutions

## General Information

---

|                                      |  |
|--------------------------------------|--|
| <b>Color</b>                         | Gray   |
| <b>Cover Type</b>                    | Clear  |
| <b>Mounting Type</b>                 | Wall Mount                                     |
| <b>Material</b>                      | Polycarbonate                                  |
| <b>Back Panel Screw Size</b>         | Plastite 48 #8                                 |
| <b>Back Panel Recommended Torque</b> | 12-16 in-lbs.                                  |
| <b>Back Panel Screw Material</b>     | 304 SS   |
| <b>Cover Screw Material</b>          | 304 SS   |
| <b>Metal Inserts</b>                 | Brass  |
| <b>Gasket Material</b>               | Poured In Place (PIP)<br>Polyurethane Seamless |
| <b>Country of Origin</b>             | Germany  |

## Dimensions

---

|                           |       |
|---------------------------|-------|
| <b>Height (in)</b>        | 8.0   |
| <b>Width (in)</b>         | 6.0   |
| <b>Depth (in)</b>         | 4.0   |
| <b>Height (mm)</b>        | 200.0 |
| <b>Width (mm)</b>         | 150.0 |
| <b>Depth (mm)</b>         | 100.0 |
| <b>Useable Depth (in)</b> | 3.5   |
| <b>Useable Depth (mm)</b> | 89.0  |

## Standards

---

|  |                            |
|--|----------------------------|
| <b>NEMA 250; UL 50; UL 50e; UL508A</b> | cULus Listed File #E64358  |
| <b>Type</b>                            | 1; 3R; 4; 4X; 12           |
| <b>IEC 60529</b>                       | IP66                       |
| <b>IEC 60529</b>                       | cULus Listed File #E362920 |
| <b>Temperature Range °F</b>            | -40°F to +212°F            |
| <b>Temperature Range °C</b>            | -40°C to +100°C            |
| <b>Flammability Rating</b>             | UL94-V2                    |
| <b>Outdoor Exposure UL746c</b>         | (f1) Rated                 |
| <b>CE</b>                              | Certified                  |