

Enclosures **Commander Series**

Polycarbonate Enclosure 5 x 3 x 3 Inches Commander Yellow Push Button 22MM Holes



Catalog Number YW-COPC2PB22

UPC 19156411713

List Price

\$108.47

Description

5H x 3W x 3D Inches Yellow Push Button Commander Series Polycarbonate Enclosures are slim-line designed enclosures featuring 4 cover screws with a lift off cover. This design has 2 holes at 22 mm.

Application

For use in many MRO and OEM applications

Features

- Memory retaining continuous polyurethane gasket
- Captive polymer cover screws on polycarbonate option
- Submersible; non corrosive; environmental design
- High Impact Resistance
- High visibility safety yellow cover
- High visibility safety yellow cover



General Information

| | |
|---------------------------------------|--|
| Color | Yellow |
| Cover Type | Push Button |
| Mounting Type | Wall Mount |
| Material | Polycarbonate |
| Cover Screw Size | Custom |
| Cover Screw Recommended Torque | 16-20 in-lbs. |
| Cover Screw Material | Polycarbonate |
| Installation Mounting Torque | 25-30 in-lbs. Max |
| Metal Inserts | |
| Gasket Material | Poured In Place (PIP) Polyurethane Seamless |
| Country of Origin | USA |

Dimensions

| | |
|---------------------------|-------|
| Height (in) | 5.0 |
| Width (in) | 3.0 |
| Depth (in) | 3.0 |
| Height (mm) | 127.0 |
| Width (mm) | 76.0 |
| Depth (mm) | 76.0 |
| Useable Depth (in) | 3.3 |
| Useable Depth (mm) | 83.0 |

Standards

| | |
|--|----------------------------|
| NEMA 250; UL 50; UL 50e; UL508A | cULus Listed File #E64358 |
| Type | 1; 3R; 4; 4X; 6; 6P; 12 |
| IEC 60529 | IP66; IP68 |
| IEC 60529 | cULus Listed File #E362920 |
| Temperature Range °F | -40°F to +248°F |
| Temperature Range °C | -40°C to +120°C |
| Flammability Rating | UL94-5VA |
| Outdoor Exposure UL746c | (f1) Rated |
| CE | Certified |