

Enclosures **Commander Series**

## Polycarbonate Enclosure 4 x 3 x 2 Inches Commander Yellow Push Button 22MM Hole



**Catalog Number** YW-COPC1PB22

**UPC** 19156411712.0

List Price

**\$99.11**

### Description

4H x 3W x 2D Inches Yellow Push Button Commander Series Polycarbonate Enclosures are slim-line designed enclosures featuring 4 cover screws with a lift off cover. This design has 1 hole at 22 mm.

### Application

For use in many MRO and OEM applications

### Features

- Memory retaining continuous polyurethane gasket
- Captive polymer cover screws on polycarbonate option
- Submersible; non corrosive; environmental design
- High Impact Resistance
- High visibility safety yellow cover
- High visibility safety yellow cover



## General Information

|                                       |  |
|---------------------------------------|--|
| <b>Color</b>                          | Yellow   |
| <b>Cover Type</b>                     | Push Button                                    |
| <b>Mounting Type</b>                  | Wall Mount                                     |
| <b>Material</b>                       | Polycarbonate                                  |
| <b>Cover Screw Size</b>               | Custom   |
| <b>Cover Screw Recommended Torque</b> | 16-20 in-lbs.                                  |
| <b>Cover Screw Material</b>           | Polycarbonate                                  |
| <b>Installation Mounting Torque</b>   | 25-30 in-lbs. Max                              |
| <b>Metal Inserts</b>                  |  |
| <b>Gasket Material</b>                | Poured In Place (PIP)<br>Polyurethane Seamless |
| <b>Country of Origin</b>              | USA  |

## Dimensions

|                           |       |
|---------------------------|-------|
| <b>Height (in)</b>        | 4.0   |
| <b>Width (in)</b>         | 3.0   |
| <b>Depth (in)</b>         | 2.0   |
| <b>Height (mm)</b>        | 102.0 |
| <b>Width (mm)</b>         | 76.0  |
| <b>Depth (mm)</b>         | 51.0  |
| <b>Useable Depth (in)</b> | 2.5   |
| <b>Useable Depth (mm)</b> | 64.0  |

## Standards

---

**NEMA 10250; UL 50; UL 50e;  
UL508A** cULus Listed File #E64358

**Type** 1; 3R; 4; 4X; 6; 6P; 12

**IEC 60529** IP66; IP68

**IEC 60529** cULus Listed File #E362920

**Temperature Range °F** -40°F to +248°F

**Temperature Range °C** -40°C to +120°C

**Flammability Rating** UL94-5VA

**Outdoor Exposure UL746c** (f1) Rated

**CE** Certified