

Accessories **HMI Covers**

## SolarShield HMI Cover 10 x 8 Inch Clear Cover

**Catalog Number** HMICVR1008C

**UPC** 19156412070

List Price

**\$208.39**

### Description

10W x 8H Inch SolarShield HMI Clear Cover for for HMI Devices offer the most innovative, durable non-metallic HMI Covers for use with all enclosure material types. The clear version has an easy to use, hinged design with clear cover which allows for visibility of the HMI screen while the cover is closed. SolarShield HMI Clear covers protect HMI screens and electrical equipment from corrosion and damage due to water, oils, dirt, and sand and greatly reduce equipment replacement cost. Impact resistant polycarbonate construction provides long dependable life in harsh conditions. The Clear Cover configuration allows for excellent visibility of the HMI screen while the cover is closed.



### Application

Provide superior protection of Human Machine Interface (HMI) screens, wind-blown dust, and other environmental conditions

### Features

- Clear Cover for visibility of HMI Display and Indicator Lights
- Fits most standard Size 10, 8, 7 and smaller HMI screens
- Maintains NEMA 4/4X rating of enclosure when paired with NEMA 4/4X rated HMI Device
- Patented with non-metallic, hinged inner doors to shield screen from the sun and allow for hands-free use

- Universal covers can be used with either non-metallic or metallic enclosures
- Lightweight, high-Impact rated, UV resistant polycarbonate material construction
- Stainless steel hardware kit Included
- Padlock-able for increased security
- Simple and easy installation with the use of common tools
- Available as standalone SKUs or assembled to our enclosures with added HMI cutouts through our value-add ModRight program.
- Inner Doors not included

## General Information

<b>Color</b>	Clear
<b>Cover Type</b>	Clear
<b>Mounting Type</b>	Box Mount
<b>Material</b>	Polycarbonate
<b>Cover Screw Size</b>	#10-32 x 5/8
<b>Cover Screw Recommended Torque</b>	20-24 in-lbs
<b>Cover Screw Material</b>	304 SS
<b>Installation Mounting Torque</b>	20-24 in-lbs Max
<b>Hinge Material</b>	Integral Polycarbonate
<b>Latch Material</b>	Nylon
<b>Gasket Material</b>	Poured In Place (PIP) Polyurethane Seamless
<b>Country of Origin</b>	India

## Dimensions

<b>Height (in)</b>	13.1
<b>Width (in)</b>	11.4
<b>Depth (in)</b>	2.5
<b>Height (in)</b>	334.0
<b>Width (in)</b>	290.0
<b>Depth (in)</b>	64.0
<b>Inside Height (in)</b>	9.9
<b>Inside Width (in)</b>	7.3
<b>Inside Depth (in)</b>	2.5

## Standards

---

<b>UL508A</b>	cULus Registered Component File #E64358
<b>Type</b>	4; 4X when Used with 4/4X HMI Device
<b>Temperature Range °F</b>	-40°F to +248°F
<b>Temperature Range °C</b>	-40°C to +120°C
<b>Flamability Rating</b>	UL94-5VA
<b>Outdoor Exposure UL746c</b>	(f1) Rated