

Enclosures **Commander Series**

## Polycarbonate Enclosure 5 x 3 x 3 Inches Commander Series Slim



**Catalog Number** **COPC533**

**UPC** **191564103884**

List Price

**\$76.26**

### Description

5H x 3W x 3D Inches Commander Series Polycarbonate Enclosures are slim-line designed enclosures featuring 4 cover screws with a blank lift off cover.

### Application

For use in many MRO and OEM applications

### Features

- Memory retaining continuous polyurethane gasket
- Captive polymer cover screws on polycarbonate option
- Submersible; non corrosive; environmental design
- High Impact Resistance



## General Information

---

<b>Color</b>	Gray
<b>Cover Type</b>	Opaque
<b>Mounting Type</b>	Wall Mount
<b>Material</b>	Polycarbonate
<b>Cover Screw Size</b>	Custom
<b>Cover Screw Recommended Torque</b>	16-20 in-lbs.
<b>Cover Screw Material</b>	Polycarbonate
<b>Installation Mounting Torque</b>	25-30 in-lbs. Max
<b>Metal Inserts</b>	
<b>Gasket Material</b>	Poured In Place (PIP) Polyurethane Seamless
<b>Country of Origin</b>	USA

## Dimensions

---

<b>Height (in)</b>	5.0
<b>Width (in)</b>	3.0
<b>Depth (in)</b>	3.0
<b>Height (mm)</b>	229.0
<b>Width (mm)</b>	76.0
<b>Depth (mm)</b>	76.0
<b>Useable Depth (in)</b>	3.3
<b>Useable Depth (mm)</b>	83.0

## Standards

---

<b>NEMA 250; UL 50; UL 50e; UL508A</b>	cULus Listed File #E64358
<b>Type</b>	1; 3R; 4; 4X; 6; 6P; 12
<b>IEC 60529</b>	IP66; IP68
<b>IEC 60529</b>	cULus Listed File #E362920
<b>Temperature Range °F</b>	-40°F to +248°F
<b>Temperature Range °C</b>	-40°C to +120°C
<b>Flammability Rating</b>	UL94-5VA
<b>Outdoor Exposure UL746c</b>	(f1) Rated
<b>CE</b>	Certified