



**Enclosures Commander Series** 

### Polycarbonate Enclosure 4 x 3 x 2 Inches Commander Push Button 22 mm Hole





**Catalog Number** 

COPC1PB22

**UPC** 

191564104034.0

List Price

\$79.28

#### **Description**

4H x 3W x 2D Inches Push Button Commander Series Polycarbonate Enclosures are slim-line designed enclosures featuring 4 cover screws with a lift off cover. This design has 1 hole at 22 mm.

#### **Application**

For use in many MRO and OEM applications

#### **Features**

- $\bullet \ \text{Memory retaining continuous polyure} than e \ \text{gasket}$
- Captive polymer cover screws on polycarbonate option
- Submersible; non corrosive; environmental design
- High Impact Resistance







#### **General Information**

| Color                             | Gray   |
|-----------------------------------|--|
| Cover Type                        | Push Button                                    |
| Mounting Type                     | Wall Mount                                     |
| Material                          | Polycarbonate                                  |
| Cover Screw Size                  | Custom   |
| Cover Screw Recommended<br>Torque | 16-20 in-lbs.                                  |
| Cover Screw Material              | Polycarbonate                                  |
| Installation Mounting Torque      | 25-30 in-lbs. Max                              |
| Metal Inserts                     |  |
| Gasket Material                   | Poured In Place (PIP)<br>Polyurethane Seamless |
| Country of Origin                 | USA  |

#### **Dimensions**

| Height (in)        | 4.0   |
|--------------------|-------|
| Width (in)         | 3.0   |
| Depth (in)         | 2.0   |
| Height (mm)        | 102.0 |
| Width (mm)         | 76.0  |
| Depth (mm)         | 51.0  |
| Useable Depth (in) | 2.5   |
| Useable Depth (mm) | 64.0  |



# **Enclosures**

## **Standards**

| NEMA 10250; UL 50; UL 50e;<br>UL508A | cULus Listed File #E64358  |
|--------------------------------------|----------------------------|
| Туре                                 | 1; 3R; 4; 4X; 6; 6P; 12    |
| IEC 60529                            | IP66; IP68                 |
| IEC 60529                            | cULus Listed File #E362920 |
| Temperature Range °F                 | -40°F to +248°F            |
| Temperature Range °C                 | -40°C to +120°C            |
| Flammability Rating                  | UL94-5VA                   |
| Outdoor Exposure UL746c              | (f1) Rated                 |
| CE                                   | Certified                  |