

Accessories **HMI Covers****SolarShield HMI Cover 10 x 8 Inch****Catalog Number** HMICVR1008**UPC** 19156411932.0

List Price

**\$208.39****Description**

10W x 8H Inch SolarShield HMI Cover for HMI Device Type 4 and 4X, Non-Metallic

**Application**

Provide superior protection of Human Machine Interface (HMI) screens from the sun, wind-blown dust, and other environmental conditions

**Features**

- Fits standard 10" x 8" and smaller HMI screens
- Maintains NEMA 4/4X rating of enclosure when paired with NEMA 4/4X rated HMI Device
- Patent pending with non-metallic, hinged inner doors to shield screen from the sun and allow for hands-free use
- Universal covers can be used with either non-metallic or metallic enclosures
- Lightweight, high-impact rated, UV resistant polycarbonate material construction
- Stainless steel hardware kit included
- Padlock-able for increased security
- Simple and easy installation with the use of common tools
- Available as standalone SKUs or assembled to our enclosures with added HMI cutouts through our value-add ModRight program.
- Color: Pantone 428C



## General Information

<b>Color</b>	Gray
<b>Cover Type</b>	Opaque
<b>Material</b>	Polycarbonate
<b>Cover Screw Size</b>	#10-32 x 5/8
<b>Cover Screw Recommended Torque</b>	20-24 in-lbs
<b>Cover Screw Material</b>	304 SS
<b>Installation Mounting Torque</b>	20-24 in-lbs Max
<b>Hinge Material</b>	Integral Polycarbonate
<b>Latch Material</b>	Nylon
<b>Gasket Material</b>	Poured In Place (PIP) Polyurethane Seamless
<b>Country of Origin</b>	India

## Dimensions

<b>Height (in)</b>	11.4
<b>Width (in)</b>	13.1
<b>Depth (in)</b>	2.5

## Standards

<b>UL508A</b>	cULus Registered Component File #E64358
UL Listed File E64358	
<b>Temperature Range °F</b>	-40°F to +248°F
<b>Temperature Range °C</b>	-40°C to +120°C
<b>Flamability Rating</b>	UL94-5VA
<b>Outdoor Exposure UL746c</b>	(f1) Rated