



#### **Enclosures BantamBox Series**

### Polycarbonate Enclosure 5 x 5 x 3 Inches BantamBox Opaque Cover



Catalog Number UPC BB121275W

List Price



### Description


5H x 5W x 3D Inches BantomBox Series polycarbonate enclosures feature flush sides making it a sought-after enclosure for OEM designs. Raised bosses accommodate back panel mounting and are sucessfully used for remote sensor mounting and small electronic controls in any environment. This conifiguration features an opaque lift off cover with 4 cover screws.

### **Application**

Small; simple design ideal for OEMs in the electronics market; circuit boards and wiring applications

#### **Features**

- Available in 2 cover options: 1. Opaque Cover; 2. Clear Polycarbonate Cover
- Multiple depths available in most sizes
- Resistant to harsh environments
- Flush sides for optimal fit
- Multiple molded in bosses for a variety of mounting solutions





A ROBROY Brand

# **Enclosures**

## **General Information**

Color	Gray
Cover Type	Opaque
Mounting Type	Wall Mount
Material	Polycarbonate
Back Panel Screw Size	Plastite 48 #8
Back Panel Recommended Torque	12-16 in-lbs.
<b>Back Panel Screw Material</b>	304 SS
Cover Screw Material	304 SS
Metal Inserts	Brass
Gasket Material	Poured In Place (PIP) Polyurethane Seamless
Country of Origin	Germany

### **Dimensions**

Height (in)	5.0
Width (in)	5.0
Depth (in)	3.0
Height (mm)	120.0
Width (mm)	120.0
Depth (mm)	75.0
Useable Depth (in)	1.7
Useable Depth (mm)	44.0



A ROBROY Brand

# **Enclosures**

## **Standards**

NEMA 250; UL 50; UL 50e; UL508A	cULus Listed File #E64358
Туре	1; 3R; 4; 4X; 12
IEC 60529	IP66
IEC 60529	cULus Listed File #E362920
Temperature Range °F	-40°F to +212°F
Temperature Range °C	-40°C to +100°C
Flammability Rating	UL94-V2
Outdoor Exposure UL746c	(f1) Rated
CE	Certified