

Enclosures **BantamBox Series****Polycarbonate Enclosure 6 x 5 x 2 Inches BantamBox Clear Cover**

Catalog Number BBCC161255W
UPC 191564105130.0

List Price

\$77.66**Description**

6H x 5W x 2D Inches BantamBox Series polycarbonate enclosures feature flush sides making it a sought-after enclosure for OEM designs. Raised bosses accommodate back panel mounting and are successfully used for remote sensor mounting and small electronic controls in any environment. This configuration features a clear lift off cover with 4 cover screws.

**Application**

Small; simple design ideal for OEMs in the electronics market; circuit boards and wiring applications

Features

- Available in 2 cover options: 1. Opaque Cover; 2. Clear Polycarbonate Cover
- Multiple depths available in most sizes
- Resistant to harsh environments
- Flush sides for optimal fit
- Multiple molded in bosses for a variety of mounting solutions

General Information

| | |
|--------------------------------------|--|
| Color | Gray |
| Cover Type | Clear |
| Mounting Type | Wall Mount |
| Material | Polycarbonate |
| Back Panel Screw Size | Plastite 48 #8 |
| Back Panel Recommended Torque | 12-16 in-lbs. |
| Back Panel Screw Material | 304 SS |
| Cover Screw Material | 304 SS |
| Metal Inserts | Brass |
| Gasket Material | Poured In Place (PIP) Polyurethane Seamless |
| Country of Origin | Germany |

Dimensions

| | |
|---------------------------|-------|
| Height (in) | 6.0 |
| Width (in) | 5.0 |
| Depth (in) | 2.0 |
| Height (mm) | 160.0 |
| Width (mm) | 120.0 |
| Depth (mm) | 55.0 |
| Useable Depth (in) | 1.7 |
| Useable Depth (mm) | 42.0 |

Standards

**NEMA 250; UL 50; UL 50e;
UL508A** cULus Listed File #E64358

Type 1; 3R; 4; 4X; 12

IEC 60529 IP66

IEC 60529 cULus Listed File #E362920

Temperature Range °F -40°F to +212°F

Temperature Range °C -40°C to +100°C

Flammability Rating UL94-V2

Outdoor Exposure UL746c (f1) Rated

CE Certified