

OSHA DRAFT VOLUNTARY FORM FOR MATERIAL SAFETY DATA SHEETS

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard
 29 CFR 1910 1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)

IDENTIFY (As Used on Label and List)
 Glass Reinforced Thermoset Polyester
 Molded Shapes of Various Colors

Note: Blank spaces are not permitted. If any information is not applicable or no information is available, the space must be marked to indicate that.

SECTION I

| | |
|---|--|
| Manufacturer's Name <p style="text-align: center;">RobRoy Industries Enclosure Division</p> Address (number, Street, City, State, & Zip Code) <p style="text-align: center;">500 Maple Street Belding, Michigan 48809</p> | Emergency Telephone Number <p style="text-align: center;">(616) 794-0700</p> Telephone Number for Information <p style="text-align: center;">(616) 794-0700</p> Date Prepared <p style="text-align: center;">Mar. 18, 1986</p> Signature of Preparer (optional) |
|---|--|

SECTION II - Hazardous Ingredients/Identity Information

N/A - This product is composed of cured polyester resin on glass substrate. TLV has not been established by the ACIGH

SECTION III - Physical/Chemical Characteristics

| | | | |
|-------------------------|---|--------------------------|------|
| Boiling Point | N/A | Specific Gravity (H2O=1) | 1.79 |
| Vapor Pressure (mm Hg) | N/A | Melting Point | N/A |
| Vapor Density (Air = 1) | N/A | Evaporation Rate | N/A |
| Solubility in water | None | | |
| Appearance and Odor | Solid shapes of various colors possible, slight sweet odor. | | |

SECTION IV - Fire and Explosion Hazard Data

| | | | | |
|---------------------------------------|---|------------------|---------|---------|
| Flash Point (method Used) | N/A | Flammable Limits | LEL N/A | UEL N/A |
| Extinguishing Media | Water preferred, may use foam. | | | |
| Special Fire Fighting Procedures | None, May be self extinguishing | | | |
| Unusual Fire and Explosion Hazards | None | | | |
| Hazardous Decomposition or Byproducts | Thermal decomposition may produce CO or CO2 | | | |

SECTION V - Health Hazard Data

Threshold Limit Value N/A

Effects of Overexposure Dust from grinding or finishing can cause mild irritation to the eyes and skin. Nuisance dust.

Emergency And First Aid Procedures Wash skin well without rubbing. For the eyes, use a sterile solution and flood the eye area. Change clothing after exposure. Apply antiseptic to abraded skin area

SECTION VI - Reactivity Data

| | | | |
|-----------|----------|---|--------------------------|
| Stability | Unstable | | Conditions To Avoid |
| | Stable | X | Extreme high temperature |

Incompatibility (Materials to Avoid) N/A

| | | | |
|----------------|----------------|---|---------------------|
| Hazardous | May Occur | | Conditions To Avoid |
| Polymerization | Will Not Occur | X | |

SECTION VII - Spill or Leak Procedures

Steps To Be Taken In Case Material Is Released Or Spilled N/A

Waste Disposal Method Abide by local laws and procedures. It is not considered hazardous waste.

SECTION VIII - Special Protection Information

Respiratory Protection (Specify Type) Dust mask when cutting.

| | | |
|-------------|-------------------|-------------------------------------|
| Ventilation | Local Exhaust | Special |
| | Well vented area. | Mechanical (General) Dust collector |
| | | Other |

Protective Gloves For handling comfort Eye Protection Safety glasses when machining.

Other Protection Cream and protective clothing while machining.

SECTION IX - Special Precautions

Precautions To Be Taken In Handling And Storing

None

Other Precautions

None